

SUBJECT 29 — DOCKET 2026-2 — APPROVED AS DOCKETED

Item	Description	Class
ELECTRICAL EQUIPMENT GROUP: subject to item 60500		
61700	Electrical Appliances, Equipment or Instruments, or Parts thereof, viz: Fans , NOI, including Exhaust or Ventilating Fans , see Note, item 61717, in boxes, crates or Package 2237; [Other Articles Listed—No Change.] Subject to Item 170 and having a density in pounds per cubic foot of:	
Sub 1	Less than 1.....	400
Sub 2	1 but less than 2.....	300
Sub 3	2 but less than 4.....	250
Sub 4	4 but less than 6.....	175
Sub 5	6 but less than 8.....	125
Sub 6	8 but less than 10.....	100
Sub 7	10 but less than 12.....	92.5
Sub 8	12 but less than 15.....	85
Sub 9	15 but less than 22.5.....	70
Sub 10	22.5 but less than 30.....	65
Sub 11	30 but less than 35.....	60
Sub 12	35 but less than 50.....	55
Sub 13	50 or greater	50
61702	NOTE—No Change.	
61703	NOTE—No Change.	
61704	NOTE—No Change.	
61705	NOTE—No Change.	
61706	NOTE—No Change.	
61707	NOTE—No Change.	
61708	NOTE—No Change.	
61709	NOTE—No Change.	
61710	NOTE—No Change.	
61711	NOTE—No Change.	
61713	NOTE—No Change.	
61714	NOTE—No Change.	
61715	NOTE—No Change.	
61716	NOTE—No Change.	
61717	NOTE—Exhaust or ventilating fans may be equipped with heating elements or lighting fixtures.	
61718	NOTE—No Change.	
61719	NOTE—No Change.	
61721	NOTE—No Change.	
61722	NOTE—No Change.	
61723	NOTE—No Change.	
61724	NOTE—No Change.	
61725	NOTE—No Change.	
61726	NOTE—No Change.	
61727	NOTE—No Change.	
61728	NOTE—No Change.	
61729	NOTE—No Change.	
61732	NOTE—No Change.	

SUBJECT 29 — DOCKET 2026-2 — APPROVED AS DOCKETED — Concluded

Item	Description	Class
	ELECTRICAL EQUIPMENT GROUP: subject to item 61700	
61733	NOTE—No Change.	
61734	NOTE—No Change.	
61735	NOTE—No Change.	
64580	Fans , NOI, ⇨other than electric, in boxes or crates100	

Comment: Item 64580 is amended to include the language “other than electric” to clarify that the provisions do not apply on electric fans.

Author: Larissa Franklin

fcdc@nmfta.org

SUBJECT 30 — DOCKET 2026-2 — APPROVED AS MODIFIED

It is proposed to amend Item 245, Definition of or Specifications for Crates, to read as follows:

Crates are six-sided containers constructed of wood or metal slats or structural members with apertures between, securely nailed, bolted, screwed, riveted or welded together, of sufficient design and strength to fully enclose and protect contents so as to withstand the normal rigors of the less-than-truckload environment. Article(s) must be secured within crates and no part shall protrude. ⇨Surfaces liable to be damaged must be fully covered and protected. All moveable contents within the crate must be blocked and/or braced to prevent any shifting during transportation. ⇨Commodities with legs must be suspended away from all edges of the crate by at least one inch. Crates must be framed to provide sufficient strength and stability to support toploaded freight of even load and weight distribution during transport, utilizing the available space above the crate, up to 96 inches, and having a density of at least 20 pounds per cubic foot. ⇨If the weight of the commodity exceeds 500 pounds, a standard crate must be used instead of a wirebound crate.

Standard wood crates must meet the following minimum specifications:

Base: Crates must have a lift truck skid, pallet or platform of sufficient design, size and strength to ensure article(s) cannot cause any failure of structural components. Deck boards must be sufficiently close to one another, or a wood structural panel (see Note 1) may be secured on top of deck boards to adequately protect article(s) from underside damage and to prevent article(s) from falling through the deck.

Note 1—Wood structural panels (plywood or oriented strand board) shall conform to DOC PS1, DOC PS2, ANSI/APA PRP 210, CSA O325 or CSA O437*.

Sides, Ends and Tops: Crates must be constructed with an outer framework consisting of upright and horizontal members and with additional diagonal, upright and horizontal members where necessary to provide proper strength and rigidity.

⇨Crate sides, ends and tops must be constructed with slats or members sufficiently close to one another to adequately protect article(s) on the sides, ends, top and bottoms, but openings on the sides, ends and tops must not exceed 24 inches in their greatest dimension, which may be the length, width, height or diagonal measurement of the opening. See Note 2.

Where present, wood structural panel(s) must be secured to frame with fasteners appropriate to prevent failure during transport.